



OVERVIEW

The Trijicon MRO (Miniature Rifle Optic) is intended for use on rifles, carbines and shotguns to provide fast target acquisition. The large aperture and tapered light path maximizes the viewing area and allows for better situational awareness. Features ambidextrous brightness controls, sub-flush adjusters, advanced lens coatings, and fully sealed, waterproof, hard anodized forged housing. The MRO is the next level in sealed mini-reflex design.

MODEL



1x25



- > **LARGE VIEWING AREA**
Allows faster target acquisition and engagement with reduced "tube effect".
- > **ADJUSTABLE BRIGHTNESS SETTINGS**
Eight brightness settings with a mid-position "Off" feature.
- > **AMBIDEXTROUS BRIGHTNESS CONTROL**
Brightness dial is equally usable by left or right-handed operators without having to remove hand from fire control.
- > **EASY-TO-SET ADJUSTERS**
Adjusters provide positive-click reticle movement in ½ MOA increments and require no special tools for operation.
- > **AIRCRAFT-GRADE ALUMINUM HOUSING**
Forged 7075 housing and fully-sealed construction protects against the toughest elements.

- > **SURFACE-FLUSH ADJUSTERS**
Capless design eliminates lost caps, snag hazards and ensures against inadvertent adjustment or loss of zero.
- > **SUPERIOR QUALITY GLASS LENSES**
Multi-coated lenses provide superior clarity and light gathering capabilities with zero distortion and provide for a crisp dot reticle.
- > **PARALLAX FREE**
- > **WATERPROOF TO 30 METERS (100 FT.)**
Dry-nitrogen filled to prevent fogging.
- > **SINGLE LITHIUM BATTERY**
5 years of continuous use at day-setting 3 (setting 5 of 8) at 70°F with supplied CR2032 lithium battery.
- > **LIMITED LIFETIME WARRANTY**
Electronics are warranted for 5 years from date of original manufacture.

The Trijicon MRO was specifically engineered with a slightly canted objective lens, allowing for a shorter optic while minimizing reflections.



BRIGHTNESS DIAL

- > **AMBIDEXTROUS DESIGN**
- > **ILLUMINATION KNOB REMOVED FROM FIELD OF VIEW**
- > **EIGHT TOTAL ILLUMINATION SETTINGS WITH TWO NIGHT VISION SETTINGS**
- > **EASY GRIP ADJUSTMENT KNURL**
- > **QUIET MOVEMENT WITH TACTILE ADJUSTMENT**



> SPECIFICATIONS

	1x25
MAGNIFICATION	1x
OBJECTIVE SIZE	25mm
CLEAR APERTURE	0.805 in. 20.4mm
EYE RELIEF	Infinite
ADJUSTMENTS	1 click = ½ MOA
ADJUSTMENT RANGE (ELEVATION AND WINDAGE)	70 MOA Total Travel
DIMENSIONS (L x W x H)	2.6 x 1.7 x 2.0 in. 66 x 43 x 51mm
WEIGHT*	4.1 oz. (w/supplied lithium battery) 116.0g
ILLUMINATION SOURCE	LED Powered by CR2032 Battery
AVAILABLE MOUNTING ADAPTERS	Picatinny Rail (in "Low", Full Co-Witness, and Lower 1/3 Co-Witness Heights)
BATTERY LIFE	5 years of continuous use** at day-setting 3
BRIGHTNESS SETTINGS	8 Total Settings 2 Night Vision, 5 Day Settings, 1 Super-Bright

*All specs given without mount.

**When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.

> 1x25

25mm Reflex-Styled Sight, 2.0 MOA Dot

Black: ■ MRO-C-2200003

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Low Mount


Black: ■ MRO-C-2200004

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Full Co-Witness Mount

Black: ■ MRO-C-2200005

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Lower 1/3 Co-Witness Mount

Black: ■ MRO-C-2200006



2.0 MOA Dot



Low Mount



Full Co-Witness Mount



Lower 1/3 Co-Witness Mount