



TRIJICON

MRO® PATROL

COMBAT-READY OUT OF THE BOX

The Trijicon MRO® PATROL continues the legendary dependability of the MRO—which is a favorite among professionals and enthusiasts alike—while also adding new innovative features. The PATROL adds lens covers for both the ocular and objective lens, along with an Anti-Reflection Device KillFlash® that protects you from unwanted detection at range or in bright conditions while eliminating glare. It features a light, strong, quick-release mount that's available in either full or lower 1/3 co-witness heights.

MODELS



1x25 MRO® PATROL

TRIJICON MRO® PATROL

FEATURES

LARGE VIEWING AREA

Allows faster target acquisition and engagement with reduced "tube effect."

AMBIDEXTROUS BRIGHTNESS CONTROL

Brightness dial is equally usable by left- or right-handed operators without having to remove hand from fire control.

ADJUSTABLE BRIGHTNESS SETTINGS

Eight brightness settings, including two night vision compatible settings with a mid-position "off" feature.

EASY-TO-SET ADJUSTERS

Adjusters provide positive-click reticle movement in ½-MOA increments and require no special tools for operation.

AIRCRAFT-GRADE ALUMINUM HOUSING

Forged 7075 housing and fully sealed construction protect against the toughest elements.

ANTI-REFLECTION DEVICE KILLFLASH®

Protects you from unwanted detection at range or in bright conditions and eliminates glare.

SUB-FLUSH ADJUSTERS

Capless design eliminates lost caps, snag hazards and ensures against inadvertent adjustment or loss of zero.

SUPERIOR QUALITY GLASS LENSES

Multi-coated lenses provide superior clarity and light-gathering capabilities with zero distortion and provide for a crisp dot reticle.

OCCULAR LENS COVER

Lens caps protect glass from damage and help reduce glare and reflection.

PARALLAX FREE

WATERPROOF TO 45 METERS (150 ft.)

Dry-nitrogen-filled to prevent fogging.

SINGLE LITHIUM BATTERY

Five years of continuous use at Day Setting 3 (setting 5 of 8) at 70°F with supplied CR2032 lithium battery.

LIMITED LIFETIME WARRANTY

Electronics are warranted for 5 years from date of original manufacture.

The Trijicon MRO® PATROL comes with ARD KILLFLASH® technology to protect from unwanted detection and eliminate glare.





TRIJICON MRO®

FAST TARGET ACQUISITION EVERY TIME

The Trijicon MRO® (Miniature Rifle Optic) is intended for use on rifles, carbines and shotguns to provide fast target acquisition. The large aperture and tapered light path maximize the viewing area and allow for better situational awareness. It also features ambidextrous brightness controls, sub-flush adjusters, advanced lens coatings, and fully sealed, waterproof, hard-anodized forged housing. The MRO is the next level in sealed mini-reflex design.

MODELS



1x25

FEATURES

LARGE VIEWING AREA

Allows faster target acquisition and engagement with reduced "tube effect."

AMBIDEXTROUS BRIGHTNESS CONTROL

Brightness dial is equally usable by left- or right-handed operators without having to remove hand from fire control.

ADJUSTABLE BRIGHTNESS SETTINGS

Eight brightness settings, including two night vision-compatible settings with a mid-position "off" feature.

EASY-TO-SET ADJUSTERS

Adjusters provide positive-click reticle movement in 1/2-MOA increments and require no special tools for operation.

AIRCRAFT-GRADE ALUMINUM HOUSING

Forged 7075 housing and fully sealed construction protects against the toughest elements.

SUB-FLUSH ADJUSTERS

Capless design eliminates lost caps, snag hazards and ensures against inadvertent adjustment or loss of zero.

SUPERIOR QUALITY GLASS LENSES

Multi-coated lenses provide superior clarity and light-gathering capabilities with zero distortion and provide for a crisp dot reticle.

PARALLAX FREE

WATERPROOF TO 45 METERS (150 ft.)
Dry-nitrogen-filled to prevent fogging.

SINGLE LITHIUM BATTERY

Five years of continuous use at Day Setting 3 (setting 5 of 8) at 70°F with supplied CR2032 lithium battery.

LIMITED LIFETIME WARRANTY

Electronics are warranted for 5 years from date of original manufacture.



The Trijicon MRO® was specifically engineered with a slightly canted objective lens, allowing for a shorter optic while minimizing reflections.



SPECIFICATIONS

SYSTEM	MRO	MRO PATROL
MAGNIFICATION	1x	1x
OBJECTIVE SIZE	25mm	25mm
CLEAR APERTURE	0.805 in. 20.4mm	0.805 in. 20.4mm
EYE RELIEF	Infinite	Infinite
ADJUSTMENTS	1 Click = ½ MOA	1 Click = ½ MOA
ADJUSTMENT RANGE {ELEVATION & WINDAGE}	70 MOA Total Travel	70 MOA Total Travel
DIMENSIONS (L X W X H)	2.6 x 1.7 x 2.0 in. 66 x 43 x 51mm	3.6 x 1.8 x 2.0 in. 91 x 43 x 51mm
WEIGHT*	4.1 oz. (w/ Supplied Lithium Battery) 116g	5.0 oz. (w/ Supplied Lithium Battery) 141.7g
ILLUMINATION SOURCE	LED Powered by CR2032 Lithium Battery	LED Powered by CR2032 Lithium Battery
AVAILABLE MOUNTING ADAPTERS	Picatinny Rail (in "Low," Full Co-Witness, and Lower 1/3 Co-Witness Heights)	Picatinny Rail (Full Co-Witness, and Lower 1/3 Co-Witness Heights)
BATTERY LIFE	5 Years of Continuous Use** at Day-Setting 3	5 Years of Continuous Use** at Day-Setting 3
BRIGHTNESS SETTINGS	8 Total Settings: 2 Night Vision, 5 Day Settings, 1 Super-Bright	8 Total Settings: 2 Night Vision, 5 Day Settings, 1 Super-Bright

*All specs given without mount.

**When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.

1x25 MRO®



25mm Reflex-Styled Sight, 2.0 MOA Dot

Black: ■ MRO-C-2200003

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Low Mount


Black: ■ MRO-C-2200004

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Full Co-Witness Mount

Black: ■ MRO-C-2200005

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Lower 1/3 Co-Witness Mount

Black: ■ MRO-C-2200006



2.0 MOA Dot

1x25 MRO® PATROL



25mm Reflex-Styled Sight, 2.0 MOA Dot


Black: ■ MRO-C-2200017

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Full Co-Witness Mount

Black: ■ MRO-C-2200019

25mm Reflex-Styled Sight, 2.0 MOA Dot w/ Lower 1/3 Co-Witness Mount

Black: ■ MRO-C-2200018



2.0 MOA Dot



Low Mount



Full Co-Witness Mount



Lower 1/3 Co-Witness Mount

ITAR ITAR controlled item. For export restrictions on all products, see page 169.
Reticles not shown to scale. For a full view of reticles, please visit our website at trijicon.com.