



# TRIJICON® **OBSERVATION**

## LET THE LONG GLASSING SESSIONS BEGIN

Trijicon® observation products have found the perfect balance between durability and weight reduction. Our legendary toughness comes standard, but so do our superior lens technology and compact designs that let you glass for as long as it takes. Whatever you need to find that hidden monster.



HD™ BINOCULARS



HD™ SPOTTING SCOPE

# TRIJICON HD™ BINOCULARS

## FEATURES

### FULLY BROADBAND, MULTI-COATED, FLUORIDE LENSES

Facilitates superior light transmission, clarity, color fidelity, and avoids chromatic aberration.

### MAGNESIUM BODY

A high-strength to low-weight ratio means a durable and lightweight binocular.

### ROOF PRISM DESIGN

Allows for a slimmer, more compact shape.

### WATERPROOF AND DRY-NITROGEN-FILLED

Stands up to all weather conditions and prevents inside lenses from fogging.

### RUBBERIZED ARMOR

Aids in a better grip and offers extra protection from rugged use and weather conditions. Unique thumb bar at the bottom allows for added grip and comfort.

### OCULAR LENS FOCUS SYSTEM

Precise image clarity can be achieved with the center focus knob and right-hand diopter ring.

### TRIPOD ADAPTER

Integrated 1/4"-20-threaded adapter allows for the addition of a tripod mount for a more stabilized sight picture during use.

### LIMITED LIFETIME WARRANTY



*A physically demanding hunt requires optics that can stand up to any element. The Trijicon HD™ Binoculars pass the test. The magnesium housing provides a strong body while the rubberized armor equips them with protection against weather elements.*



## SPECIFICATIONS

SYSTEM	8X42	10X42
MAGNIFICATION	8x	10x
OBJECTIVE LENS	42mm	42mm
FIELD OF VIEW	384 ft. @ 1000 yds. 128m @ 1000m	351 ft. @ 1000 yds. 117m @ 1000m
FIELD OF VIEW (DEGREES)	6.7°	6.1°
EYE RELIEF	0.87 in. 22mm	0.67 in. 17mm
CLOSE FOCUS DISTANCE	9.8 ft. 3.0m	8.4 ft. 2.6m
EXIT PUPIL DIAMETER	0.21 in. 5.3mm	0.17 in. 4.2mm
TWILIGHT FACTOR	18.3	20.5
LIGHT TRANSMISSION	85% +	85% +
INTERPUPILLARY DISTANCE	2.2 – 2.9 in. 56 – 74mm	2.2 – 2.9 in. 56 – 74mm
DIOPTIC CORRECTION (D)	±3	±3
TRIPOD THREAD	¼" – 20	¼" – 20
DIMENSIONS (L X W X H)	6.1 x 5.2 x 2.2 in. 155 x 132 x 55mm	6.1 x 5.2 x 2.2 in. 155 x 132 x 55mm
WEIGHT (WITHOUT CAPS AND HARNESS)	24.7 oz. 700.0g	24.3 oz. 690.0g
WATERPROOF	10 mins. @ 6.5 ft. 10 mins. @ 2m	10 mins. @ 6.5 ft. 10 mins. @ 2m

### 8x42



8x42 HD™ Binoculars with Harness and Lens Covers  
 TBN01-C-2000000

### 10x42



10x42 HD™ Binoculars with Harness and Lens Covers  
 TBN02-C-2000001

# TRIJICON HD™ SPOTTING SCOPE

## FEATURES

### FULLY BROADBAND, MULTI-COATED, FLUORIDE LENSES

Featuring fluoride lens elements facilitating superior light transmission, clarity, color fidelity, and avoids chromatic aberration.

### MAGNESIUM CONSTRUCTION

Incorporating a magnesium body allows maximum strength and reduces the overall weight for a durable, highly portable, and lightweight spotting scope.

### WATERPROOF AND DRY-NITROGEN-FILLED

Stands up to all weather conditions and prevents inside lenses from fogging.

### RUBBERIZED ARMOR

Aids in a better grip and offers extra protection from the elements and active use.

### DUAL-FOCUS KNOBS

Located on the top center of the scope, coarse and fine-focus knobs allow easy finger adjustments for quick and precise focusing.

### ANGLED EYEPIECE WITH BODY INDEXING FEATURE

The angled eyepiece is more ergonomic and maximizes the user's comfort while the body indexing feature allows 225° vertical rotation of the spotting scope to move eyepiece position without adjusting the tripod.

### TRIPOD ADAPTER

Integrated at the base of the spotting scope to allow for use with most tripods; recommended for a more stabilized sight picture during use.

### LIMITED LIFETIME WARRANTY

*The Trijicon HD™ Spotting Scope features a tripod collar allowing the scope body to rotate 225° for viewing at many angles. This works especially well for bench rest shooters who want to view their shot groups at long distances. The rotating collar has an indexing feature with tactile detents, positioning the scope at various angles.*



# TRIJICON HD™ SPOTTING SCOPE

## SPECIFICATIONS

	20 – 60X	25 – 50X
MAGNIFICATION RANGE	20 – 60x	25 – 50x
OBJECTIVE LENS	82mm	N/A
FIELD OF VIEW	105 – 63 ft. @ 1000 yds. 35 – 21m @ 1000m	126 – 81 ft. @ 1000 yds. 42 – 27m @ 1000m
FIELD OF VIEW (DEGREES)	2° – 1.2°	2.4° – 1.5°
APPARENT FIELD OF VIEW	40° – 65°	N/A
EYE RELIEF	0.73 in. 18.5mm	0.669 in. 17mm
LIGHT TRANSMISSION	80% +	N/A
CLOSE FOCUS	19.5 ft. 5.9m	N/A
EXIT PUPIL DIAMETER	0.16 in. – 0.06 in. 4.05mm – 1.4mm	0.130 – 0.063 in. 3.3 – 1.6mm
TRIPOD THREAD	1/4"–20	N/A
LENGTH	15.13 in. 384.2mm	N/A
WEIGHT (WITHOUT CAPS AND CASE)	63.9 oz. 1811g	10.2 oz. 290g
COATING	N/A	Fully Broadband, Multi-Coated
WATERPROOF	30 mins. @ 3.3 ft. 30 mins. @ 1m	N/A

### 20-60x82



Trijicon 20-60x82 HD™ Spotting Scope with Caps, Hard and Soft Carrying Cases  
TSS01-C-2100000

### 25-50X WIDE-ANGLE LENS



Trijicon HD™ Spotting Scope Eyepiece - 25-50x Wide Angle  
AC70005

**ITAR** ITAR controlled item. For export restrictions on all products, see page 169.  
Reticles not shown to scale. For a full view of reticles, please visit our website at [trijicon.com](http://trijicon.com).