



TRIJICON  
SRS®

## SHORT BODY. SERIOUS TECHNOLOGY.

The Trijicon SRS® (Sealed Reflex Sight) is a uniquely designed, MIL-spec-rugged, parallax-free reflex sight which incorporates a larger aperture for maximum situational awareness in a shorter body. The illuminated 1.75 MOA red dot with 10 brightness settings (3 NVG compatible) is powered by a single AA battery, assisted by a solar cell to extend battery life. The snag-free button pads make brightness adjustments easy and eliminate fumbling under stress or with gloves.

### MODELS



1x38 (with Thumb-Screw Mount)



1x38 (with Quick-Release Mount)

## FEATURES

### HYBRID-ILLUMINATED RETICLE

Powered by a combination of a single AA battery, assisted by a solar cell to extend battery life.

### RUGGED ALUMINUM-ALLOY HOUSING

Forged 7075-T6 aircraft-aluminum-alloy housing provides for a nearly indestructible sighting system.

### SINGLE AA-ALKALINE OR LITHIUM BATTERY

Over 3 years of continuous use at brightness setting 7 of 10 at 70°F with supplied lithium battery, even in dark storage.

### EASY PUSH BUTTONS

The brightness adjustment buttons are designed to be easily manipulated and accessible.

### MANUALLY ADJUSTABLE BRIGHTNESS CONTROL

10 brightness settings, including 3 night vision and 1 super-bright. A visible dot—no matter the lighting conditions.

### MULTI-LAYER BROADBAND ANTI-REFLECTIVE COATING

Parallax-free, 38mm objective lens provides a larger field of view. Unique lens design helps create a much shorter optic.

### PARALLAX-FREE

### WATERPROOF TO 50 METERS (165 ft)

Dry-nitrogen-filled to prevent fogging.

### SHOCK RESISTANT

Designed to withstand shock from various weapon platforms.

### LIMITED LIFETIME WARRANTY

Electronics are warranted for 5 years from date of original manufacture.

*The Trijicon SRS® features a photovoltaic cell, or in layman's terms, a solar panel. This solar panel utilizes ambient light to assist in reticle illumination and helps extend the battery life.*



## SPECIFICATIONS

SYSTEM	1X38
MAGNIFICATION	1x
OBJECTIVE SIZE	38mm
CLEAR APERTURE	1.1 in. 28mm
FIELD OF VIEW	69 ft. @ 100 yds. (w/ 4 in. Eye Relief) 23m @ 100m (w/ 4 in. Eye Relief)
ADJUSTMENTS	1 Click = 1/2 MOA
ADJUSTMENT RANGE (ELEVATION AND WINDAGE)	150 MOA Total Travel
DIMENSIONS (L X W X H)	3.75 x 2.5 x 2.4 in. (w/o Mount) 95 x 64 x 61mm
WEIGHT	10.9 oz. (w/ Supplied Lithium Battery and w/o Mount) 310g
ILLUMINATION SOURCE	LED Powered by a Single AA Alkaline or Lithium Battery Assisted by a Solar Panel
BATTERY LIFE	3+ Years Continuous Use at Brightness Setting 7 of 10* (Lithium Battery) 2.5+ Years Continuous Use at Brightness Setting 7 of 10* (Alkaline Battery)
BRIGHTNESS SETTINGS	10 Total Settings: NV 1, NV 2, NV 3, Day 1, Day 2, Day 3, Day 4, Day 5, Day 6, Super-Bright
PHOTOVOLTAIC CELL	Provides Supplemental Power when in Daylight Conditions, Further Increasing Battery Life


\*When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.

### 1x38 (with Thumb-Screw Mount)



38mm Sealed Reflex Sight, 1.75 MOA Dot with Thumb-Screw Mount

Black: ■ SRS01




1.75 MOA Dot

### 1x38 (with Quick-Release Mount)



38mm Sealed Reflex Sight, 1.75 MOA Dot with Quick-Release Mount

Black: ■ SRS02



1.75 MOA Dot

ITAR ITAR controlled item. For export restrictions on all products, see page 169.  
Reticles not shown to scale. For a full view of reticles, please visit our website at [trijicon.com](http://trijicon.com).