



Trijicon®

TRIJICON ACCUPOINT®

Variable Powered Sporting Rifle Scope



> **BATTERY-FREE ILLUMINATION**

Fiber optic technology automatically adjusts the brightness level and contrast of the reticle aiming point to available light conditions and a tritium phosphor lamp illuminates the reticle in low to no light.

> **AIRCRAFT-GRADE ALUMINUM HOUSING**

All-weather rugged construction protects against the toughest elements.

> **SUPERIOR QUALITY LENSES**

Multi-coated lenses provide superior clarity and light gathering capabilities with zero distortion.

> **SECOND FOCAL PLANE RETICLE**

Reticle size remains constant as magnification increases which provides a more exact aiming point at higher magnifications.

> **EASY-FOCUS EYEPIECE**

> **ZERO FORWARD EMISSION**

The illuminated reticle doesn't project any illumination from the objective lens.

> **EASY-TO-SET ADJUSTERS**

> **MATTE BLACK FINISH**

Eliminates glare and light reflection.

> **WATERPROOF TO 10 FT. (3M)**

Dry-nitrogen filled to eliminate fogging.

> **LIMITED LIFETIME WARRANTY**

Tritium lamp is warranted to illuminate for 15 years from date of original manufacture.

MANUAL BRIGHTNESS OVERRIDE




All AccuPoint® models feature a manual brightness override.



MODEL SPECIFICATIONS

	3-9x40 (TR20 SERIES)	2.5-10x56 (TR22 SERIES)	5-20x50 (TR23 SERIES)	1-4x24 (TR24 SERIES)	1-6x24 (TR25 SERIES)	2.5-12.5x42 (TR26 SERIES)	4-16x50 (TR29 SERIES)
EYE RELIEF	3.6 – 3.2 in. 91.4 – 81.3mm	4.1 – 2.8 in. 104 – 71mm	3.8 – 4.1 in. 96 – 103mm	3.2 in. Constant 81.3mm Constant	3.9 in. Constant 100mm Constant	3.9 in. Constant 100mm Constant	3.6 – 3.7 in. 92 – 93mm
EXIT PUPIL	0.52 – 0.17 in. 13.2 – 4.3mm	0.64 – 0.22 in. 16.3 – 5.6mm	0.39 – 0.10 in. 10 – 2.5mm	0.69 – 0.20 in. 17.5 – 5.1mm	0.47 – 0.16 in. 12 – 4.1mm	0.42 – 0.13 in. 10.6 – 3.3mm	0.37 – 0.12 in. 9.3 – 3.1mm
FIELD OF VIEW (DEGREES)	6.5' – 2.2'	7.2' – 1.9'	3.7' – 1.0'	18.0' – 4.6'	21.4' – 3.6'	7.8' – 1.6'	4.9' – 1.2'
FIELD OF VIEW	34.0 – 11.5 ft. @ 100 yds. 11.3 – 3.8m @ 100m	37.7 – 9.9 ft. @ 100 yds. 12.6 – 3.3m @ 100m	19.4 – 5.2 ft. @ 100 yds. 6.5 – 1.8m @ 100m	94.2 – 24.1 ft. @ 100 yds. 31.4 – 8.0m @ 100m	117.5 – 18.8 ft. @ 100 yds. 39.2 – 6.3m @ 100m	41.3 – 8.3 ft. @ 100 yds. 13.8 – 2.8m @ 100m	25.8 – 6.4 ft. @ 100 yds. 8.6 – 2.1m @ 100m
ADJUSTMENTS (@100 YDS.)	1/4 in. per click	1/4 in. per click	1/4 MOA per click	1/4 in. per click	1/4 MOA per click 0.1 MIL per click	1/4 MOA per click 0.1 MIL per click	1/4 MOA per click 0.1 MIL per click
ADJUSTMENT RANGE	50 MOA Total Travel	60 MOA Total Travel	40 MOA Total Travel	90 MOA Total Travel	110 MOA Total Travel 32.6 MIL Total Travel	90 MOA Total Travel 26.7 MIL Total Travel	80 MOA Total Travel 23.7 MIL Total Travel
PARALLAX ADJUSTMENT RANGE	N/A	N/A	40 yds. to Infinity	N/A	N/A	10 yds. to Infinity	10 yds. to Infinity
DIMENSIONS (L x W x H)	12.4 x 1.9 x 1.9 in. 315 x 47 x 47mm	13.8 x 2.6 x 2.6 in. 351 x 65 x 65mm	13.6 x 3.2 x 3.2 in.* 345 x 82 x 82mm	10.3 x 2.0 x 2.0 in. 262 x 50 x 50mm	11.0 x 2.0 x 2.0 in. 280 x 50 x 50mm	13.8 x 2.4 x 2.3 in. 351 x 61 x 58mm	13.9 x 2.5 x 2.5 in. 353 x 63.5 x 63.5mm
WEIGHT	13.4 oz. 379.9g	20.7 oz. 586.8g	26.9 oz.* 762.6g	14.4 oz. 408.2g	19.2 oz. 545.0g	22.4 oz. 635.0g	24.2 oz. 685g
TUBE DIAMETER	1 in.	30mm	30mm	30mm	30mm	30mm	30mm


*w/out included sunshade



Triangle Post




1-4x24 (TR24 Series)
1-6x24 (TR25 Series)
2.5-10x56 (TR22 Series)
2.5-12.5x42 (TR26 Series)
3-9x40 (TR20 Series)
5-20x50 (TR23 Series)
4-16x50 (TR29 Series)



German #4 Crosshair




1-4x24 (TR24 Series)
1-6x24 (TR25 Series)



Std Duplex Crosshair




1-4x24 (TR24 Series)
1-6x24 (TR25 Series)
2.5-10x56 (TR22 Series)
2.5-12.5x42 (TR26 Series)
3-9x40 (TR20 Series)
5-20x50 (TR23 Series)
4-16x50 (TR29 Series)



MIL-Dot Crosshair




1-6x24 (TR25 Series)
2.5-10x56 (TR22 Series)
2.5-12.5x42 (TR26 Series)
3-9x40 (TR20 Series)
5-20x50 (TR23 Series)
4-16x50 (TR29 Series)



MOA-Dot



1-6x24 (TR25 Series)
2.5-12.5x42 (TR26 Series)
4-16x50 (TR29 Series)



Circle Cross



1-6x24 (TR25 Series)

Note: Reticles enlarged to show detail.

WWW.TRIJICON.COM

©2017 Trijicon, Inc. | Wixom, Michigan USA | Phone: 1-800-338-0563 | info@trijicon.com | Specifications subject to change without notice. | PML4013-2 Rev(4) 0717