

Trijicon[®]

Brilliant Aiming Solutions[™]



Instruction Card

TRIJICON MRO[®] COVER

CAUTIONS

1. Before installing the MRO[®] Cover on your optic, ensure the weapon is UNLOADED per the weapon manufacturer's operating instructions. Remove the ammunition, open the action, and ensure the chamber is clear.

INSTALLATION

Step 1. Begin by placing the objective (down range) end of the Trijicon MRO® through the rectangular opening at the bottom of the cover.



Step 2. Pull the cover backwards over the MRO[®] towards the ocular end (shooter side) of the optic, be sure the cover fits snugly over the azimuth (windage) adjuster and brightness adjustment knob.



Step 3. Remove clear lenses from plastic bags.

Step 4. Place the clear lenses into the inside of each cap, the lenses will seat flush to the inside of the cap with an audible click.



Step 5. Fold the caps over the ocular and objective end of the optic and check they fit securely without obstructing the aiming solution.



The Trijicon MRO® cover should now be correctly installed. For additional support please contact Trijicon customer support at www.trijicon.com or 1-800-338-0563.

NOTE: With the lenses installed and the caps open, the ocular end of the MRO cover nests inside the objective end of the cover to secure the caps alongside the optic.



WWW.TRIJICON.COM

© 2016 Trijicon, Inc. | PML6022 Rev(1) 1116